

## PSC 0200 DuraWax-Gloss

PSC 0200 DuraWax is a water based, high solids premium wax providing a crystal-clear, rich wet look; a high gloss finish without burnishing. The clarity and leveling abilities of the product allow for easy traffic line touch ups without re-coating the entire floor.

The high percentage of solids in the product makes the floors treated with PSC 0200 feel soft, abrasion resistant and highly slip resistant. PSC 0200 is a coating for all types of resilient and hard floors, including natural stone, ceramic tiles, wood and concrete.

PSC 0200 DuraWax is approved by CFIA (Canadian Food Inspection Agency) for use in Registered Establishments handling and processing food stuffs.

### Uses

- Shopping malls, retail outlets, restaurants, hotels.
- Commercial and municipal applications, hospitals, museums.
- For concrete substrates, industrial and decorative applications.
- For all kind of stone, ceramic tile and hardwood.

### Advantages

- Makes floors scuff, abrasion and slip resistant.
- Due to high percentage of solids, hides scratches on surfaces coated with epoxy or urethane coatings.
- Easy to use, no burnishing necessary.

### General data

Mass solids	25 %
Specific weights	1.0 g / cm <sup>3</sup> (8.3 lbs. / gallon)
VOC	4 – 8 grams / Liter
Flash point	Not applicable
Color	Clear
Finish	Gloss
Method of application	Mop
Thinner	Dilution of the product is not required
Cleaner	Use water and soap

### Surface preparation

Ensure that the surface is structurally sound, clean and dry. Porous surfaces like concrete, concrete overlays and wood must be sealed with an appropriate sealer.

### Application

Apply 3 to 5 coats of PSC 0200 DuraWax-Gloss to a sealed surface using a mop. Allow each coat to dry before applying the next coat. Optional burnishing will increase the gloss and hardness slightly.

For re-coating, clean the floor thoroughly with PSC 0150 Cleaner Rejuvenator, rinse and apply 1 to 3 coats of PSC 0200 DuraWax-Gloss. Burnishing is optional. The clarity and leveling abilities of the product allow for easy traffic lane touch-ups without re-coating the entire floor.

Floors can be restored by regularly cleaning with PSC 0150 Cleaner Rejuvenator.

### Coverage

Typical coverage per coat varies from 3,500 to 5,000 sq. ft./gallon. Coverage varies with the method of application, surface texture and porosity.

### Cure schedule

Temperature	Drying time	Re-coating
10 C (50 F)	10 to 20 minutes	Re-coat after

20 C (68 F)	5 to 10 minutes	previous coat
30 C (86 F)	2 to 5 minutes	has dried

Using floor fans can reduce the drying time. Allow wax to level for 2 minutes before using fans. Do not aim the fans directly at the floor.

#### Limitations

- Do not use the product at temperatures below 10 C (50 F).
- Protect from freezing.

#### Storage

Store product under cool and dry conditions. Protect from freezing.

#### Safety precautions

- Avoid skin and eye contact.
- Provide adequate ventilation.
- In case of skin contact, wash thoroughly with soap and lukewarm water.
- In case of eye contact, flush with water for 15 minutes and seek medical attention.

Prior to handling this product, consult the labels of the containers and for more detailed information the Material Safety Data Sheets (MSDS).

#### Packaging

5 USG Pails

#### Warranty Disclaimer

We guarantee our Products to conform to the specifications of Polymer Science Corporation. Polymer Science Corporation makes no warranty or guarantee, express or implied, including warranties of fitness for a particular purpose or merchantability, respecting its Products. Liability, if any, is limited to refund of purchase price or replacement of the Product. All consequential damages, labor and cost of labor are hereby excluded.

**For orders or inquiries from Canada, US and Mexico, call toll free 1-866-793-3503 or fax your orders to PSC's customer service at 403-287-2766.**

**Polymer Science Corporation develops and manufactures specialty chemicals, industrial and architectural coatings of highest quality. Ask the people who use them.**